

3 loop fire alarms

Data sheet

AATS4081 - AATS4082

Technical Department

Tél. : +33 (0) 160 215 125
Fax : +33 (0) 160 215 128
E-mail : technique@cordia.fr

Sales Department

Tel: +33 (0) 160 215 130
Fax: +33 (0) 160 215 139
E-mail: contact@cordia-fire-safety.com

www.myfiresafetyproducts.com



AATS4081



AATS4082



- Mains powered.
- 3 loops.
- Beacon.

Applications

All buildings except if automatic detectors required.

Associated products

- Manual callpoint (ADMR8001).
- Sounder (ADIS0013).
- Sounder beacon (ADSV0013).
- Industrial sounder beacon (TDSV0001).
- External power supply (AALS2425).

3 loop fire alarms

Data sheet

AATS4081 - AATS4082

Technical Department

Tél. : +33 (0) 160 215 125
Fax : +33 (0) 160 215 128
E-mail : technique@cordia.fr

Sales Department

Tel: +33 (0) 160 215 130
Fax: +33 (0) 160 215 139
E-mail: contact@cordia-fire-safety.com

www.myfiresafetyproducts.com



AATS4081



AATS4082

Technical characteristics

Power supply	230 V / 50 Hz
Secondary power supply	3 batteries 1.2 V Ni/MH 2000 mAh
Number of manual callpoint loops	3
Max. number of manual callpoints per loop	32
Sounder output	16 V / 200 mA maximum
IP rating	IP 30
Flashing light	4 LEDs, 6 candelas
Auxiliary relay	1 NO/NC (24 V / 1 A)
Fault relay	1 NO/NC (24 V / 1 A)

Part number	AATS4081	AATS4082
Manual callpoint	-	Resettable, with hinged cover
Evacuation signal	-	Sound + flash
Tone*	-	English
Weight	800 g	900 g
Dimensions	W.180 x H.275 x D.55 mm	W.180 x H.275 x D.55 mm

*Other tones available on request.